

# Tendeurs à rochet

L = largeur sangle en mm  
R = rupture danN/kg

A = longueur totale (mm)  
B = largeur totale (mm)  
C = largeur levier (mm)  
P = poids (g)



L 75  
R 10 000  
A 320  
B 138  
C 104  
P 3 250

Référence : 975



L 50  
R 5 000  
A 250  
B 91  
C 95  
P 1 200

Référence : ERGO PP



L 50  
R 5 000  
A 235  
B 91  
C 97  
P 1 230

Référence : 811 SVR



L 50  
R 5 000  
A 235  
B 92  
C 95  
P 1 100

Référence : 811 PP



L 50  
R 5 000  
A 235  
B 92  
C 95  
P 1 100

Référence : 811 PPA



L 50  
R 5 000  
A 165  
B 92  
C 74  
P 1 060

Référence : 910



L 50  
R 2 000  
A 133  
B 80  
C 79  
P 530

Référence : 916



L 50  
R 4 000  
A 147  
B 90  
C 57  
P 700

Référence : 914  
Référence : 914 H




L 35  
R 4 000  
A 157  
B 77  
C 55  
P 780

Référence : 908




L 35  
R 2 000  
A 134  
B 66.5  
C 67  
P 410

Référence : 917



L 25  
R 1 500  
A 134  
B 55  
C 54  
P 390

Référence : 909 WH



L 25  
R 700  
A 113  
B 50  
C 37  
P 210

Référence : 906



L 50  
R 5 000  
A 235  
B 92  
C 95  
P 1 100

Référence : 811 PP inox



L 35  
R 2 000  
A 134  
B 66  
C 73  
P 440

Référence : 917 inox



L 25  
R 700  
A 113  
B 50  
C 37  
P 210

Référence : 906 inox




L 45  
R 1 500  
A 224  
B 60  
P 490

Référence : FA



L 45  
R 2 250  
A 168  
B 65  
P 555

Référence : 913



L 50  
R 2 000  
A 140  
B 62  
P 340

Référence : 912

## Boucles



L 50  
R 600  
A 57  
B 68  
P 105

Référence : 802



L 50  
R 1 80  
A 45  
B 75  
P 80

Référence : 806



L 35  
R 800  
A 60  
B 47  
P 120

Référence : 804



L 25  
R 600  
A 50  
B 44  
P 66

Référence : 801



L 25  
R 350  
A 50  
B 32  
P 68

Référence : 803

**S I M A**

**G-17**